THE WHIRLPOOL SYSTEM SHOULD BE CLEANED PERIODICALLY. ATLANTIC WHIRLPOOLS RECOMMENDS CLEANING TUBS LEAST ONCE A MONTH - NOT TO EXCEED 90 DAYS BETWEEN CLEANINGS. ALWAYS USE CAUTION WHEN USING CHLORINE-BASED PRODUCTS IN CONJUNCTION WITH OTHER CLEANING PRODUCTS. THE POSSIBILITY OF HARMFUL FUMES COULD RESULT. ALWAYS RINSE THOROUGHLY.

Fill tub with warm water 2" above the highest jet and add one of the following to the bath water:

Several drops of a low sudsing detergent mixed with 1 cup warm water. Turn the system on for five minutes then let stand for an additional 15 minutes. Drain the tub and refill with cold water. Restart the system for 10 minutes then drain.

CLEANING INSTRUCTIONS FOR THE ACRYLIC SHELL

With normal use, cast acrylic will retain its beauty with only a minimal amount of care. To maintain the gloss look of the cast acrylic surface, follow these steps:

- 1. Use common household, non-abrasive cleaners for most cleaning jobs (For example: Greased Lightning, Glass Plus, Simple Green, Mr. Clean, Top Job, or a mild dishwashing detergent such as Ivory Liquid.) Follow manufacturers' directions and precautions. Rinse well and dry with a soft, clean cloth.
- 2. Never use abrasive cleansers. If any product feels gritty when rubbed between your fingers, do not use on the acrylic surface or controls as permanent damage will occur.
- 3. Do not allow your cast acrylic surface to come into contact with nail polish, nail polish remover, Wintergreen oil, dry cleaning solution, lacquer thinners, gasoline, pine oil, etc.
- 4. Remove dust and dry dirt with a soft, damp cloth.
- 5. Clean grease, oil, paint or ink stains with isopropyl (rubbing) alcohol. Dry with a clean, soft cloth.
- 6. Avoid using razor blades or other sharp objects that might scratch the surface. Small scratches can be removed by applying a thin coat of automotive paste wax and buffing lightly with a clean cloth. For deeper scratches, sand the surface lightly with a 400 grit "wet or dry" paper and buff with a fine grit buffing compound.

ATLANTIC WHIRLPOOLS STRONGLY RECOMMENDS A PROFESSIONAL ACRYLIC REPAIR PERSON FOR DEEP SCRATCHES OR CHIPS.